

- Rib pattern design maximizes hydroplaning resistance and minimizes irregular wear
- Engineered for high-load applications, the M8008 tread compound is specially formulated to minimize heat generation and incorporates premium antioxidant agents for superior weather protection and durability
- Sidewall construction engineered to operate under high load-cycles and improve trailer stability
- Premium inner liner compound minimizes diffusion air loss, allowing the M8008 to run longer at optimal inflation pressures
- Premium dual-cord body casing design dramatically improves casing strength for superior durability and toughness
- Unique apex rubber design features a softer compound to absorb shock and minimize heat generation during high-load operations
- Select sizes feature additional cap reinforcement layer for class-leading durability

SPECS

MAXXIS

13.0"

14.0"

ST205/75R14

Part #	TL00097400
SIZE	ST205/75R14
SERVICE DESCRIPTION	100/96N
Load Range	C
SIDEWALL	BSW
OVERALL DIAMETER (IN)	26.1
SECTION WIDTH (IN)	8.11
MAX PSI	50
MAX LOAD (LBS)	1,760
TREAD DEPTH (IN)	9/32

ST205/75R14

Part #	TL00097500
SIZE	ST205/75R14
SERVICE DESCRIPTION	105/101N
Load Range	D
SIDEWALL	BSW
OVERALL DIAMETER (IN)	26.1
SECTION WIDTH (IN)	8.03
MAX PSI	65
MAX LOAD (LBS)	2,040
TREAD DEPTH (IN)	9/32

ST215/75R14

Part #	TL00097600
SIZE	ST215/75R14
SERVICE DESCRIPTION	102/98N
Load Range	C
SIDEWALL	BSW