



BOAT, CARGO, HORSE AND LIVESTOCK, RV, TOWABLE UTILITY, AND SPECIALTY TRAILERS

USA TRAIL® (continued)

SIZE	PRODUCT CODE	LOAD RANGE	DIAMETER†	WIDTH†	RIM WIDTH	MAX CAPACITY	TIRE PSI*	TREAD DEPTH (32nds)	SPEED RATING
18.5x8.50-8	519472	LRC	17.7	8.5	7.00	935	50	10	62
6.90-9	519572	LRC	22.0	7.1	4.50	1100	60	10	62
20.5x8.00-10	519141	LRB	21.0	8.4	6.00	910	35	10	62
20.5x8.00-10	519142	LRC	20.7	8.5	6.00	1100	50	10	62
20.5x8.00-10	519143	LRD	20.5	8.6	6.00	1320	70	10	62
20.5x8.00-10	519144	LRE	20.9	8.7	6.00	1520	90	10	62
4.80-12	519062	LRB	21.0	5.0	4.00	785	60	8	62
4.80-12	519063	LRC	21.3	5.1	4.00	990	90	8	62
5.30-12	519076	LRB	21.8	5.3	4.00	855	55	8	62
5.30-12	519077	LRC	22.1	5.3	4.00	1050	80	8	87
ST175/80D13	519161	LRC	25.0	6.7	4.50	1360	50	10	65
ST195/75D14**	519307	LRD	24.6	7.2	5.50	1870	65	10	62
ST195/75D14**	519306	LRC	24.9	7.2	5.50	1610	50	10	62
ST205/75D14	519300	LRC	26.0	8.3	5.50	1760	50	10	65
ST215/75D14	519315	LRC	26.4	8.4	6.00	1870	50	10	65
ST205/75D15	519400	LRC	27.1	8.0	5.50	1820	50	10	65
ST225/75D15	519410	LRC	28.1	8.9	6.00	2150	50	10	65
ST225/75D15	519412	LRD	28.6	9.0	6.00	2540	65	10	65

† Indicates mounted diameter and mounted width

*NOTE: Tire PSI shown is the Recommended PSI

**NOTE: Sizes with asterisks have the Sure Trail tread pattern. Made in the USA.

***Note: Sizes with asterisks have the Extra Grip tread pattern.

CSL 16 ALL STEEL

The CSL 16 tire offers heavy duty hauling capabilities for large equipment and extremely heavy loads. Its all-steel body is essential for a load rating of up to 4,400 pounds of towing capacity. Its robust construction combined with an industrial highway tread design leads to extended service life on the highway and protects against environmental elements.

SIZE	PRODUCT CODE	LOAD RANGE	DIAMETER†	WIDTH†	RIM WIDTH	MAX CAPACITY	TIRE PSI*	TREAD DEPTH (32nds)	SPEED RATING
ST235/80R16	6H08101	G	30.6	9.2	6.50	4080/3640	110	12	81
ST235/85R16	6H08111	G	31.7	9.3	6.50	4400/3850	110	11.6	81